

SAF-T-LOK

International Corporation

Material Safety Data Sheet
SOLVENTLESS PRIMER

Issue Date: 10/20/2016

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: SOLVENTLESS PRIMER
Product Type: Anaerobic Adhesive Primer
Part Numbers: **19218, 19277**
Hazard Rating: Health: 1 Fire: 1 Reactivity: 0

Company Identification: SAF-T-LOK International Corporation
300 EISENHOWER LANE NORTH
LOMBARD, IL 60148

Contact: Helen Sherry
Telephone/ Fax: (630) 495-2001
Emergency Phone (24 Hour): (703) 527-3887
Chemtrec (24 Hour): (800) 424-9300
Preparer: Ind. Hygiene Department
Internet: www.saftlok.com

Product Class: Mixture
DOT Hazard Class: N/A
Shipping Name: N/A

SECTION II - INGREDIENT AND HAZARD INFORMATION

<u>Components</u>	<u>Percent</u>
Methacrylic Ester Monomers	85-95
Copper Napthanate	0.1-5.0

SECTION III - HAZARD IDENTIFICATION AND EMERGENCY OVERVIEW

EMERGENCY OVERVIEW

Physical appearance:	Green Liquid	<u>HMS</u>	
		Health:	1
		Flammability:	1
		Reactivity:	0
		Personal Protection:	B

WARNING; MAY CAUSE: EYE IRRITATION
SKIN IRRITATION
RESPIRATORY TRACT IRRITATION
MAY IRRITATE EXISTING ALLERGIC SKIN CONDITIONS

Relative routes of entry: Skin, Inhalation, Eyes

Skin Contact: Irritating to skin. Prolonged contact can dry and defat the skin, causing the skin to crack, leading to dermatitis.

Eye Contact: Vapors may irritate eyes. Contact with eyes will cause redness and irritation.

Respiratory/ Inhalation: May cause respiratory tract irritation. Symptoms of excessive exposure are irritation of nose and throat, dizziness, headache, and nausea.

Ingestion: Amounts transferred to mouth by fingers, etc, during normal operation should not cause injury. Low oral toxicity level.

Medical conditions generally aggravated by exposure: Eye, skin, and respiratory disorders.

SECTION IV – FIRST AID INSTRUCTIONS

Skin Contact: Remove contaminated clothing. Wash affected area with soap and rinse with plenty of water. Get medical attention if symptoms occur. Wash clothing before reuse.

Eye Contact: Flush with water for at least 15 minutes holding eyelid open. Get medical attention.

Respiratory / Inhalation: Remove to fresh air, if symptoms develop get medical attention.

Ingestion: Do not induce vomiting. If conscious, drink plenty of water. Obtain medical attention if symptoms develop.

SECTION V – FIRE FIGHTING INSTRUCTIONS

Flash Point: 208°F (TCC)

Unusual Fire and Explosion Hazards: N/A

Flammable Limits: LEL: N/A, UEL: N/A

Extinguishing Media: Carbon Dioxide, Foam, Dry Chemicals, Water spray

Fire Fighting Procedures: As in any fire, wear self-contained breathing apparatus and full protective clothing.

SECTION VI -ACCIDENTAL RELEASE MEASURES

Special Precautions: Ventilate area. Remove all sources of ignition.

Environmental precautions: Prevent material from entering floor drains, sewers, or any bodies of water.

Clean up methods: Clean up area with absorbent material. Store in a closed container until disposal. Obey relevant local, state, provincial and federal laws and regulations.

SECTION VII - HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin, and clothing. Avoid breathing vapors and mist. Wash hands thoroughly at mealtime and end of shift. Keep area ventilated.

Storage: Store in a cool location (60-90°F) in a well ventilated area away from sources of heat or other sources of ignition.

Personal Protection: Wear personal protective equipment as outlined in Section VIII of this MSDS.

SECTION VIII – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory Protection: Use NIOSH approved respirator if used in confined spaces.

Skin Protection: Use impermeable gloves (neoprene, butyl rubber, natural rubber), as necessary to avoid skin contact, as well as proper clothing or plastic apron. Wash hands before eating, drinking, or using restroom.

Eye Protection: Safety goggles or safety glasses with side shields..

Eye Washes: Eye wash stations should be located within 100 feet or 10 second walk of the work area.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Green liquid
Odor: Mild
Boiling Point: >300°F
Specific Gravity: 1.1
Vapor Density (Air = 1): N/D
Vapor Pressure (mm Hg.): <5 @30°F
pH: N/A
Melting Point: N/A
Evaporation Rate: N/A
Solubility in Water: Partial

SECTION X –STABILITY AND REACTIVITY

Stability: Stable
Hazardous Polymerization: Will not occur.
Hazardous decomposition byproducts: May produce fumes when heated to decomposition. Fumes may contain carbon monoxide
Incompatibility: Strong oxidizing and reducing agents

SECTION XI – TOXICOLOGICAL INFORMATION

Carcinogen Status
NTP Carcinogen: No IARC Monographs: No OSHA Regulated: No

SECTION XII – ECOLOGICAL DATA

Do not allow to enter soil, waterways, or waste water.

SECTION XIII – DISPOSAL CONSIDERATIONS

Recommended method of disposal: Dispose of according to Federal, State and local regulations.

SECTION XIV – SHIPPING AND TRANSPORTATION INFORMATION

U.S. Department of Transportation Ground (49 CFR)
International Air Transportation (ICAO/ IATA)
Water Transportation (IMO/IMDG)
Not subject to the regulations on dangerous goods.

SECTION XV – REGULATORY INFORMATION

United States Regulatory Information

Not Restricted

All components of this product are listed on the Toxic Substance Control Act (TSCA) inventory of chemical substances maintained by the U.S. Environmental Protection Agency.

Canada Regulatory Information

CEPA, DSL/ NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

SECTION XVI – OTHER INFORMATION

Revision date: 10/20/2016

DISCLAIMER: The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.